

Wall-Mount Multi-Zone Indoor

9K-24 BTU



ASUH09KPAS - ASUH12KPAS



ASUH18KPAS - ASUH24KPAS



Built In Filtration

 **LONG-LIFE ION DEODORIZATION FILTER** 

The filter deodorizes by powerfully decomposing absorbed odors using the oxidizing and reducing effects of ions generated by the ultra-fine-particle ceramic. The filter can be used for approximately 3 years if it is washed with water when dirty to restore its surface action.

 **APPLE-CATECHIN FILTER** 

Dust, mold spores and micro-organisms are absorbed onto the filter by static electricity so growth is inhibited and deactivated.

- 
- 
- 
- 
- 
- 
- 
- 
- 
- 
- 
- 
- 
- 

- 
- 
- 


Hand held remote control included with indoor unit

* Applies to products that have been properly installed and registered by a participating Fujitsu Elite Contractor in a residence. See full Fujitsu warranty for details.

** Wi-Fi connectivity with Airstage Mobile App monitoring via compatible USB WLAN adapter.



OLDACH
REFRIGERATION, AIR CONDITIONING & VENTILATION SUPPLIER



Product Specifications

Multi-Zone Indoor			ASUH09KPAS	ASUH12KPAS		ASUH18KPAS	ASUH24KPAS
Performance							
Rated Cooling	BTU/h		9,000	12,000		18,000	24,000
Rated Heating	BTU/h		9,000	12,000		18,000	24,000
Fan (Cooling Mode)							
Air Circulation: Hi	CFM (m3/h)		412 (700)	412 (700)		577 (980)	689 (1,170)
Med.- High	CFM (m3/h)		371 (630)	371 (630)		524 (890)	594 (1,010)
Medium	CFM (m3/h)		330 (560)	330 (560)		477 (810)	500 (850)
Med.- Low	CFM (m3/h)		288 (490)	288 (490)		424 (720)	436 (740)
Low	CFM (m3/h)		253 (430)	253 (430)		377 (640)	377 (640)
Quiet	CFM (m3/h)		159 (270)	159 (270)		300 (510)	300 (510)
Fan Speed Stages	CFM (m3/h)		6+Auto	6+Auto		6+Auto	6+Auto
Sound							
Indoor Level (Clg/Htg): Hi	dB(A)		40/42	40/42		45/46	49/49
Med.- High	dB(A)		38/39	38/39		43/44	45/44
Medium	dB(A)		34/36	35/38		40/40	40/40
Med.- Low	dB(A)		32/34	32/35		37/37	37/37
Low	dB(A)		29/31	30/33		35/35	35/35
Quiet	dB(A)		21/22	21/22		29/29	29/29
Electrical							
Voltage/Frequency/Phase			208/230 V ~ 60 Hz	208/230 V ~ 60 Hz		208/230 V ~ 60 Hz	208/230 V ~ 60 Hz
Current Rated/Max: Clg	Amps		0.35/ 0.44	0.35/ 0.44		0.35/ 0.44	0.35/ 0.44
Current Rated/Max: Htg	Amps		0.35/ 0.44	0.35/ 0.44		0.35/ 0.44	0.35/ 0.44
Input Power	W		21.8	21.8		40.0	63.0
Size & Weight							
Net Weight	lbs. (kg)		21 (9.5)	21 (9.5)		28 (12.5)	28 (12.5)
Dimensions: Height	Inch		10-5/8	10-5/8		11	11
	mm		270	270		280	280
Width	Inch		32-13/16	32-13/16		38-9/16	38-9/16
	mm		834	834		980	980
Depth	Inch		8-3/4	8-3/4		9-7/16	9-7/16
	mm		222	222		240	240
Refrigerant			R-32	R-32		R-32	R-32
Additional Data							
Air Direction: Horizontal			Manual	Manual		Manual	Manual
Air Direction: Vertical			Automatic	Automatic		Automatic	Automatic
Air Filter Type			Washable	Washable		Washable	Washable
Ion Deodorizing Filter			Disposable	Disposable		Disposable	Disposable
Apple-Catechin Filter			Disposable	Disposable		Disposable	Disposable
Lineset Size	Inch		Gas 3/8 Liq. 1/4	Gas 3/8 Liq. 1/4		Gas 1/2 Liq. 1/4	Gas 1/2 Liq. 1/4

AIRSTAGE



ENERGY STAR® Qualified

- When paired with a qualifying condensing unit

Oldach Associates, LLC. | Rev.(B) 5/2025

Actual product color may be different from the colors shown here.

Product specifications as presented belong to the manufacturer. Specifications and design are subject to change without notice.

